





The EcoLite™ incorporates essential features with Casio's Industry Leading LampFree® Technology to create a budget friendly projector. The XJ-V1 delivers reliable long term operation, exceptional image quality, 2700 lumens of brightness & connectivity and is ideal for use in classrooms, on the road or in the boardroom.

LampFree Benefits:

- Laser & LED Hybrid Light source
- 20,000 estimate operating life
- Mercury Free
- No Lamp Replacement
- No Down Time
- Quick ON full brightness in 5 seconds
- Instant Off

Key Features:

- Laser & LED Hybrid Light source
- Brightness: 2700 lumens
- Resolution: XGA (1024 x 768)
- Display Device: 0.55" DLP® chip × 1, DLP® system
- Lens: 1.1 x Manual Zoom/FocusThrow Ratio: 1.54-1.71:1
- Terminals:
 - RGB (15 pin HD)
 - HDMI
 - RS-232 (9 pin D-Sub)
 - Audio (3.5mm stereo Mini Variable Audio Out
- Dimensions: 10.6"w x 10.6"d x 3.5"h
 Ceiling Mount: Yes Four (4) M4 x 4

Reliable Operation and Low TCO:

Casio LampFree® Projectors are reliable and built to last, with an estimated light source life of up to 20,000 hours. The EcoLite is covered by a 3-year parts and labor warranty plus 3 years or 6,000 hours on the Hybrid Light Source. Our industry leading warranty makes our already low Total Cost of Ownership (TCO) even better and users can expect to easily save up to \$1000 on lamp cost during the warranty period.



Native Resolution	XGA (1024 x 768) 786,432 pixels
Native Aspect Ratio	4:3
Brightness	2700 lumens
Display Device	0.55" DLP® chip
Contrast Ratio	20000:1
(Full White/Black)	
Lens Type	1.1X Manual Zoom & Focus
Lens Offset	72%
Light Source	Casio Laser & LED Hybrid
Estimated Light Source Life	Up to 20,000 hours
Projection Screen Size (Min-Max)	36 - 360 inches
Projection Range	
60-inch Screen	5.9-6.5 ft
100-inch screen	10.1-11.2 ft
Minimum	2.7 ft @30inch 1
Throw Ratio	1.54-1.71:1
Keystone Correction	Vertical + or - 30° (Manual)
Color Reproduction	Full color (up to 1.07 billion colors)
Power Source	AC 100 ~240V, 50/60 Hz
Power Consumption	
Operating	~155w Eco Off Bright Mode
Standby	0.15w
TERMINAL CONNECTIVITY	
Video Signal Compatibility	
Video Systems	NTSC/ PAL/ PAL-N/ PAL-M/ PAL60/ SECAM
DTV/HDTV	480i/480p/576i/576p/720p/1080i/1080p
Maximum Computer Input	UXGA (1600 x 1200)
INPUTS	
RGB/Component Video Input	"mini D-Sub 15 pin x 1 also use as YCbCr/YPbPr input
	commercially available adapter required"
HDMI	"HDMI Type A x 1 (480p~1080p) HDCP and audio support"
Composite Video	No
Audio	3.5 mm Mini - Stereo
Microphone	No
USB	No
USB Wireless Capability	
USB Wireless Capability OUTPUTS	No No
USB Wireless Capability OUTPUTS Audio	No No 3.5 mm Mini - Stereo Variable Audio
USB Wireless Capability OUTPUTS Audio RGB Output	No No
USB Wireless Capability OUTPUTS Audio RGB Output AUDIO AND CONTROL SYSTEMS	No No 3.5 mm Mini - Stereo Variable Audio
USB Wireless Capability OUTPUTS Audio RGB Output AUDIO AND CONTROL SYSTEMS Control Terminal	No No 3.5 mm Mini - Stereo Variable Audio No
USB Wireless Capability OUTPUTS Audio RGB Output AUDIO AND CONTROL SYSTEMS Control Terminal RS-232	No No 3.5 mm Mini - Stereo Variable Audio No RS-232 (Dsub 9 Pin) x 1
USB Wireless Capability OUTPUTS Audio RGB Output AUDIO AND CONTROL SYSTEMS Control Terminal RS-232 LAN	No No 3.5 mm Mini - Stereo Variable Audio No
USB Wireless Capability OUTPUTS Audio RGB Output AUDIO AND CONTROL SYSTEMS Control Terminal RS-232 LAN OTHER INFORMATION	No No 3.5 mm Mini - Stereo Variable Audio No RS-232 (Dsub 9 Pin) x 1
USB Wireless Capability OUTPUTS Audio RGB Output AUDIO AND CONTROL SYSTEMS Control Terminal RS-232 LAN OTHER INFORMATION Usage Environment	No No 3.5 mm Mini - Stereo Variable Audio No RS-232 (Dsub 9 Pin) x 1 No
USB Wireless Capability OUTPUTS Audio RGB Output AUDIO AND CONTROL SYSTEMS Control Terminal RS-232 LAN OTHER INFORMATION Usage Environment Operating Temperature	No No 3.5 mm Mini - Stereo Variable Audio No RS-232 (Dsub 9 Pin) x 1 No 41~95°F
USB Wireless Capability OUTPUTS Audio RCB Output AUDIO AND CONTROL SYSTEMS Control Terminal RS-232 LAN OTHER INFORMATION Usage Environment Operating Temp/Humidity Operating Temp/Humidity	No No No 3.5 mm Mini - Stereo Variable Audio No RS-232 (Dsub 9 Pin) x 1 No 41~95°F 20~80% (non condensation)
USB Wireless Capability OUTPUTS Audio RGB Output AUDIO AND CONTROL SYSTEMS Control Terminal RS-232 LAN OTHER INFORMATION Usage Environment Operating Temp/Humidity High Altitude Mode	No No No No 3.5 mm Mini - Stereo Variable Audio No RS-232 (Dsub 9 Pin) x 1 No 41~95°F 20~80% (non condensation) Yes (for operation 5,000 to 10,000ft above sea level)
USB Wireless Capability OUTPUTS Audio RGB Output AUDIO AND CONTROL SYSTEMS Control Terminal RS-232 LAN OTHER INFORMATION Usage Environment Operating Temp/Humidity High Altitude Mode	No No No 3.5 mm Mini - Stereo Variable Audio No RS-232 (Dsub 9 Pin) x 1 No 41~95°F 20~80% (non condensation) Yes (for operation 5,000 to 10,000ft above sea level) Yes
USB Wireless Capability OUTPUTS Audio RCB Output AUDIO AND CONTROL SYSTEMS Control Terminal RS-232 LAN OTHER INFORMATION Usage Environment Operating Temperature Operating Temp/Humidity High Altitude Mode Extended operation (24 x 7)	No No No No 3.5 mm Mini - Stereo Variable Audio No RS-232 (Dsub 9 Pin) x 1 No 41~95°F 20~80% (non condensation) Yes (for operation 5,000 to 10,000ft above sea level) Yes Note: Projector must be turned off once every 24 hours
USB Wireless Capability OUTPUTS Audio RGB Output AUDIO AND CONTROL SYSTEMS Control Terminal RS-232 LAN OTHER INFORMATION Usage Environment Operating Temp/Humidity High Altitude Mode Extended operation (24 x 7) Rotation Projection	No No No No 3.5 mm Mini - Stereo Variable Audio No RS-232 (Dsub 9 Pin) x 1 No 41~95°F 20~80% (non condensation) Yes (for operation 5,000 to 10,000ft above sea level) Yes Note: Projector must be turned off once every 24 hours No
USB Wireless Capability OUTPUTS Audio RGB OUTPUTS Audio RGB OUTPUTS Control Terminal RS-232 LAN OTHER INFORMATION Usage Environment Operating Temperature Operating Temp/Humidity High Altitude Mode Extended operation (24 x 7) Rotation Projection Closed Captioning	No No No No 3.5 mm Mini - Stereo Variable Audio No RS-232 (Dsub 9 Pin) x 1 No 41~95°F 20~80% (non condensation) Yes (for operation 5,000 to 10,000ft above sea level) Yes Note: Projector must be turned off once every 24 hours No No
USB Wireless Capability OUTPUTS Audio RCB Output AUDIO AND CONTROL SYSTEMS Control Terminal RS-232 LAN OTHER INFORMATION Usage Environment Operating Temperature Operating Temp/Humidity High Altitude Mode Extended operation (24 x 7) Rotation Projection Closed Captioning Remote Control Range	No No No No 3.5 mm Mini - Stereo Variable Audio No RS-232 (Dsub 9 Pin) x 1 No 41~95°F 20~80% (non condensation) Yes (for operation 5,000 to 10,000ft above sea level) Yes Note: Projector must be turned off once every 24 hours No No No
USB Wireless Capability OUTPUTS Audio RGB Output AUDIO AND CONTROL SYSTEMS Control Terminal RS-232 LAN OTHER INFORMATION Usage Environment Operating Temp/Humidity High Altitude Mode Extended operation (24 x 7) Rotation Projection Closed Captioning Remote Control Range Security Compatibility	No No No No 3.5 mm Mini - Stereo Variable Audio No RS-232 (Dsub 9 Pin) x 1 No 41~95°F 20~80% (non condensation) Yes (for operation 5,000 to 10,000ft above sea level) Yes Note: Projector must be turned off once every 24 hours No No TBA Kensington™ Compatible / Power On Password
USB Wireless Capability OUTPUTS Audio RGB Output AUDIO AND CONTROL SYSTEMS Control Terminal RS-232 LAN OTHER INFORMATION Usage Environment Operating Temperature Operating Temp/Humidity High Altitude Mode Extended operation (24 x 7) Rotation Projection Closed Captioning Remote Control Range Security Compatibility Ceiling Mountable	No No No No No 3.5 mm Mini - Stereo Variable Audio No RS-232 (Dsub 9 Pin) x 1 No 41~95°F 20~80% (non condensation) Yes (for operation 5,000 to 10,000ft above sea level) Yes Note: Projector must be turned off once every 24 hours No No No TBA Kensington™ Compatible / Power On Password Yes, available and sold separately by 3rd party vendors
USB Wireless Capability OUTPUTS Audio RGB OUDTA AUDIO AND CONTROL SYSTEMS Control Terminal RS-232 LAN OTHER INFORMATION Usage Environment Operating Temperature Operating Temp/Humidity High Altitude Mode Extended operation (24 x 7) Rotation Projection Closed Captioning Remote Control Range Security Compatibility Ceiling Mountable Ceiling Mount Screws (Type x Qty)	No No No No 3.5 mm Mini - Stereo Variable Audio No RS-232 (Dsub 9 Pin) x 1 No 41~95°F 20~80% (non condensation) Yes (for operation 5,000 to 10,000ft above sea level) Yes Note: Projector must be turned off once every 24 hours No No TBA Kensington™ Compatible / Power On Password Yes, available and sold separately by 3rd party vendors M4 x 4 (not included) Insert depth (5-8 mm)
USB Wireless Capability OUTPUTS Audio RGB OUDTA AUDIO AND CONTROL SYSTEMS Control Terminal RS-232 LAN OTHER INFORMATION Usage Environment Operating Temperature Operating Temp/Humidity High Altitude Mode Extended operation (24 x 7) Rotation Projection Closed Captioning Remote Control Range Security Compatibility Ceiling Mountable Ceiling Mount Screws (Type x Qty)	No No No No 3.5 mm Mini - Stereo Variable Audio No RS-232 (Dsub 9 Pin) x 1 No 41~95°F 20~80% (non condensation) Yes (for operation 5,000 to 10,000ft above sea level) Yes Note: Projector must be turned off once every 24 hours No No TBA Kensington™ Compatible / Power On Password Yes, available and sold separately by 3rd party vendors M4 x 4 (not included) Insert depth (5-8 mm) 3 Years Parts & Labor plus 3 years or 6,000 hours on light source, see
USB Wireless Capability OUTPUTS Audio RGB Output AUDIO AND CONTROL SYSTEMS Control Terminal RS-232 LAN OTHER INFORMATION Usage Environment Operating Temperature Operating Temp/Humidity High Altitude Mode Extended operation (24 x 7) Rotation Projection Closed Captioning Remote Control Range Security Compatibility Ceiling Mountable Ceiling Mount Screws (Type x Qty) Limited Warranty	No No No No 3.5 mm Mini - Stereo Variable Audio No RS-232 (Dsub 9 Pin) x 1 No 41~95°F 20~80% (non condensation) Yes (for operation 5,000 to 10,000ft above sea level) Yes Note: Projector must be turned off once every 24 hours No No TBA Kensington™ Compatible / Power On Password Yes, available and sold separately by 3rd party vendors M4 x 4 (not included) Insert depth (5-8 mm) 3 Years Parts & Labor plus 3 years or 6,000 hours on light source, see Warranty Statement included with product for complete details
USB Wireless Capability OUTPUTS Audio RGB OUTPUTS Audio ALDIO AND CONTROL SYSTEMS Control Terminal RS-232 LAN OTHER INFORMATION Usage Environment Operating Temperature Operating Temp/Humidity High Altitude Mode Extended operation (24 x 7) Rotation Projection Closed Captioning Remote Control Range Security Compatibility Ceiling Mountable Ceiling Mount Screws (Type x Qty) Limited Warranty Included Accessories	No No No No No 3.5 mm Mini - Stereo Variable Audio No RS-232 (Dsub 9 Pin) x 1 No 41~95°F 20~80% (non condensation) Yes (for operation 5,000 to 10,000ft above sea level) Yes Note: Projector must be turned off once every 24 hours No No TBA Kensington™ Compatible / Power On Password Yes, available and sold separately by 3rd party vendors M4 x 4 (not included) Insert depth (5-8 mm) 3 Years Parts & Labor plus 3 years or 6,000 hours on light source, see Warranty Statement included with product for complete details Remote Control, Power Cord, RGB Cable, Warranty, Setup Guide
USB Wireless Capability OUTPUTS Audio RGB Output AUDIO AND CONTROL SYSTEMS Control Terminal RS-232 LAN OTHER INFORMATION Usage Environment Operating Temp/Humidity High Altitude Mode Extended operation (24 x 7) Rotation Projection Closed Capitioning Remote Control Range Security Compatibility Ceiling Mountable Ceiling Mount Screws (Type x Qty) Limited Warranty Included Accessories Optional Accessories	No No No 3.5 mm Mini - Stereo Variable Audio No RS-232 (Dsub 9 Pin) x 1 No 41~95°F 20~80% (non condensation) Yes (for operation 5,000 to 10,000ft above sea level) Yes Note: Projector must be turned off once every 24 hours No No TBA Kensington™ Compatible / Power On Password Yes, available and sold separately by 3rd party vendors M4 x 4 (not included) Insert depth (5-8 mm) 3 Years Parts & Labor plus 3 years or 6,000 hours on light source, see Warranty Statement included with product for complete details Remote Control, Power Cord, RGB Cable, Warranty, Setup Guide TBA
USB Wireless Capability OUTPUTS Audio RGB Output AUDIO AND CONTROL SYSTEMS Control Terminal RS-232 LAN OTHER INFORMATION Usage Environment Operating Temp/Humidity High Altitude Mode Extended operation (24 x 7) Rotation Projection Closed Captioning Remote Control Range Security Compatibility Ceiling Mount Screws (Type x Qty) Limited Warranty Included Accessories Optional Accessories Cabinet Color	No No No No No 3.5 mm Mini - Stereo Variable Audio No RS-232 (Dsub 9 Pin) x 1 No 41~95°F 20~80% (non condensation) Yes (for operation 5,000 to 10,000ft above sea level) Yes Note: Projector must be turned off once every 24 hours No No TBA Kensington™ Compatible / Power On Password Yes, available and sold separately by 3rd party vendors M4 x 4 (not included) Insert depth (5-8 mm) 3 Years Parts & Labor plus 3 years or 6,000 hours on light source, see Warranty Statement included with product for complete details Remote Control, Power Cord, RGB Cable, Warranty, Setup Guide
USB Wireless Capability OUTPUTS Audio RGB OUDTO AND CONTROL SYSTEMS Control Terminal RS-232 LAN OTHER INFORMATION Usage Environment Operating Temperature Operating Temp/Humidity High Altitude Mode Extended operation (24 x 7) Rotation Projection Closed Captioning Remote Control Range Security Compatibility Ceiling Mountable Ceiling Mount Screws (Type x Qty) Limited Warranty Included Accessories Optional Accessories Optional Accessories Cabinet Color Dimension (W x D x H)	No No No No 3.5 mm Mini - Stereo Variable Audio No RS-232 (Dsub 9 Pin) x 1 No 41~95°F 20~80% (non condensation) Yes (for operation 5,000 to 10,000ft above sea level) Yes Note: Projector must be turned off once every 24 hours No No No TBA Kensington™ Compatible / Power On Password Yes, available and sold separately by 3rd party vendors M4 x 4 (not included) Insert depth (5-8 mm) 3 Years Parts & Labor plus 3 years or 6,000 hours on light source, see Warranty Statement included with product for complete details Remote Control, Power Cord, RGB Cable, Warranty, Setup Guide TBA White
USB Wireless Capability OUTPUTS Audio RGB Output AUDIO AND CONTROL SYSTEMS Control Terminal RS-232 LAN OTHER INFORMATION Usage Environment Operating Temperature Operating Temp/Humidity High Altitude Mode Extended operation (24 x 7) Rotation Projection Closed Captioning Remote Control Range Security Compatibility Ceiling Mountable Ceiling Mountable Ceiling Mount Screws (Type x Qty) Limited Warranty Included Accessories Optional Accessories Cabinet Color Dimension (W x D x H) Including Projections	No No 3.5 mm Mini - Stereo Variable Audio No RS-232 (Dsub 9 Pin) x 1 No 41~95°F 20~80% (non condensation) Yes (for operation 5,000 to 10,000ft above sea level) Yes Note: Projector must be turned off once every 24 hours No No TBA Kensington™ Compatible / Power On Password Yes, available and sold separately by 3rd party vendors M4 x 4 (not included) Insert depth (5-8 mm) 3 Years Parts & Labor plus 3 years or 6,000 hours on light source, see Warranty Statement included with product for complete details Remote Control, Power Cord, RGB cable, Warranty, Setup Guide TBA White
USB Wireless Capability OUTPUTS Audio RGB Output AUDIO AND CONTROL SYSTEMS Control Terminal RS-232 LAN OTHER INFORMATION Usage Environment Operating Temp/Humidity High Altitude Mode Extended operation (24 x 7) Rotation Projection Closed Captioning Remote Control Range Security Compatibility Ceiling Mountable Ceiling Mountable Ceiling Mount Screws (Type x Qty) Limited Warranty Included Accessories Optional Accessories Optional Accessories Cabinet Color Dimension (W x D x H) Including Projections Excluding Projections	No No No No 3.5 mm Mini - Stereo Variable Audio No RS-232 (Dsub 9 Pin) x 1 No 41~95°F 20~80% (non condensation) Yes (for operation 5,000 to 10,000ft above sea level) Yes Note: Projector must be turned off once every 24 hours No No TBA Kensington™ Compatible / Power On Password Yes, available and sold separately by 3rd party vendors M4 x 4 (not included) Insert depth (5-8 mm) 3 Years Parts & Labor plus 3 years or 6,000 hours on light source, see Warranty Statement included with product for complete details Remote Control, Power Cord, RGB Cable, Warranty, Setup Guide TBA White 10.6″ x 10.6″ x 3.5″ TBA
USB Wireless Capability OUTPUTS Audio RGB Output AUDIO AND CONTROL SYSTEMS Control Terminal RS-232 LAN OTHER INFORMATION Usage Environment Operating Temperature Operating Temp/Humidity High Altitude Mode Extended operation (24 x 7) Rotation Projection Closed Captioning Remote Control Range Security Compatibility Ceiling Mountable Ceiling Mount Screws (Type x Qty) Limited Warranty Included Accessories Optional Accessories Optional Accessories Cabinet Color Dimension (W x D x H) Including Projections Excluding Projections Weight	No No 3.5 mm Mini - Stereo Variable Audio No RS-232 (Dsub 9 Pin) x 1 No 41~95°F 20~80% (non condensation) Yes (for operation 5,000 to 10,000ft above sea level) Yes Note: Projector must be turned off once every 24 hours No No TBA Kensington™ Compatible / Power On Password Yes, available and sold separately by 3rd party vendors M4 x 4 (not included) Insert depth (5-8 mm) 3 Years Parts & Labor plus 3 years or 6,000 hours on light source, see Warranty Statement included with product for complete details Remote Control, Power Cord, RGB cable, Warranty, Setup Guide TBA White
USB Wireless Capability OUTPUTS Audio RGB Output AUDIO AND CONTROL SYSTEMS Control Terminal RS-232 LAN OTHER INFORMATION Usage Environment Operating Temperature Operating Temp/Humidity High Altitude Mode Extended operation (24 x 7) Rotation Projection Closed Captioning Remote Control Range Security Compatibility Ceiling Mountable Ceiling Mountable Ceiling Mount Screws (Type x Qty) Limited Warranty Included Accessories Optional Accessories Optional Accessories Cabinet Color Dimension (W x D x H) Including Projections Excluding Projections Excluding Projections Weight Packing Information	No No No 3.5 mm Mini - Stereo Variable Audio No RS-232 (Dsub 9 Pin) x 1 No 41~95°F 20~80% (non condensation) Yes (for operation 5,000 to 10,000ft above sea level) Yes Note: Projector must be turned off once every 24 hours No No TBA Kensington™ Compatible / Power On Password Yes, available and sold separately by 3rd party vendors M4 x 4 (not included) Insert depth (5-8 mm) 3 Years Parts & Labor plus 3 years or 6,000 hours on light source, see Warranty Statement included with product for complete details Remote Control, Power Cord, RGB cable, Warranty, Setup Guide TBA White 10.6" x 10.6" x 3.5" TBA 8.6 lbs
USB Wireless Capability OUTPUTS Audio RGB Output AUDIO AND CONTROL SYSTEMS Control Terminal RS-232 LAN OTHER INFORMATION Usage Environment Operating Temperature Operating Temp/Humidity High Altitude Mode Extended operation (24 x 7) Rotation Projection Closed Captioning Remote Control Range Security Compatibility Ceiling Mountable Ceil	No No No No 3.5 mm Mini - Stereo Variable Audio No RS-232 (Dsub 9 Pin) x 1 No 41-95°F 20-80% (non condensation) Yes (for operation 5,000 to 10,000ft above sea level) Yes Note: Projector must be turned off once every 24 hours No No TBA Kensington™ Compatible / Power On Password Yes, available and sold separately by 3rd party vendors M4 x 4 (not included) Insert depth (5-8 mm) 3 Years Parts & Labor plus 3 years or 6,000 hours on light source, see Warranty Statement included with product for complete details Remote Control, Power Cord, RGB Cable, Warranty, Setup Guide TBA White 10.6" x 10.6" x 3.5" TBA 8.6 lbs
USB Wireless Capability OUTPUTS Audio RGB Output AUDIO AND CONTROL SYSTEMS Control Terminal RS-232 LAN OTHER INFORMATION Usage Environment Operating Temp/Humidity High Altitude Mode Extended operation (24 x 7) Rotation Projection Closed Captioning Remote Control Range Security Compatibility Ceiling Mountable Ceiling Mountable Ceiling Mountable Ceiling Mount Screws (Type x Qty) Limited Warranty Included Accessories Optional Accessories Optional Accessories Cabinet Color Dimension (W x D x H) Including Projections Excluding Projections Excluding Projections Weight Packing Information	No No No 3.5 mm Mini - Stereo Variable Audio No RS-232 (Dsub 9 Pin) x 1 No 41~95°F 20~80% (non condensation) Yes (for operation 5,000 to 10,000ft above sea level) Yes Note: Projector must be turned off once every 24 hours No No TBA Kensington™ Compatible / Power On Password Yes, available and sold separately by 3rd party vendors M4 x 4 (not included) Insert depth (5-8 mm) 3 Years Parts & Labor plus 3 years or 6,000 hours on light source, see Warranty Statement included with product for complete details Remote Control, Power Cord, RGB cable, Warranty, Setup Guide TBA White 10.6" x 10.6" x 3.5" TBA 8.6 lbs

© 2015 Casio America, Inc. All rights reserved. Casio is a registered trademark of Casio Computer Co., Ltd. In the United States and/or other countries. Specifications were thought to be correct at time of publication. All specifications and features are subject to change without notice. DLP, the DLP logo and the DLP medalillon are trademarks of lexas instruments. XGA and WXGA are registered trademarks of International Business Machines Corporation in the United States. HDMI is a trademark or registered trademark of HDMI Licensing, LLC. Other product names or company names on this specification brochure are either trademarks or registered trademarks of their respective owners.